

JZ-600-Y-CY flexible, number coded, 0,6/1kV, Cu screened meter marking, EMC-preferred type



A



Technical data

- Special control cables with thermoplastic PVC insulation On the basis of DIN VDE 0262/12.95 and DIN VDE 0281 part 13
- **Temperature range**
flexing -5°C to +80°C
fixed installation -40°C to +90°C
- **Nominal voltage** U_0/U 0,6/1 kV
- **Test voltage** 4000 V
- **Breakdown voltage** min. 8000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Power rating**
according to DIN VDE 0298
- **Minimum bending radius**
flexing 10x cable \emptyset
fixed installation 5x cable \emptyset
- **Radiation resistance**
up to 80×10^6 cJ/kg (up to 80 Mrad)
- **Coupling resistance**
max. 250 Ohm/km

Cable structure

- Bare copper, fine wire conductors, according to DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Special PVC core insulation T12, to DIN VDE 0281 part 1
- Black cores with sequential numbering imprinted in white, according to DIN VDE 0293
- Green-yellow earth core in the outer layer (3 cores and above)
- Cores stranded in layers with optimal lay-length
- PVC-insulated inner sheath
- Braided screen of tinned Cu wires, coverage approx. 85%
- Special PVC outer sheath TM2, to DIN VDE 0281 part 1
- colour black (RAL 9005)
- with meter marking, change-over in 2009

Properties

- Extensively oil resistant
- Chemical Resistance - see table Technical Informations
- PVC self-extinguishing and flame retardant according to VDE 0482-332-1-2, DIN EN 60332-1-2/ IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers
- Resistant to ultra violet rays

Note

- G = with green-yellow earth core;
x = without green-yellow earth core (OZ).
- Further sizes are available upon request.
- AWG sizes are approximate equivalent values. The actual cross-section is in mm².
- **unscreened analogue type:**
JZ-600, see page A 17

Application

Wiring cable for measuring and controlling purposes in tool machinery, conveyor belts and production lines, for plant installations, air conditioning and in steel production plants and rolling mills. Suitable for installation for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms as well as outside (fixed installation). Is not suitable to be used as direct burrial- or as underwater cable. The cores have been numbered in such a way that the numbers are easily identifiable, even if the cable has only been stripped back a few cm. The core numbers have been underlined to avoid confusion. The earth core is located in the outer layer. The black, special PVC outer sheath is resistant to the ultra violet radiation. Mainly used in South-European, Eastern and Arabian countries. Interference-free transmission of signals and pulses is assured by the high degree of screening.

EMC = Electromagnetic compatibility

To optimise the EMC features we recommend a large round contact of the copper braiding on both ends.

CE = The product is conformed with the EC Low-Voltage Directive 2006/95/EG.

Part No.	No. cores x cross-sec. mm ²	Outer \emptyset app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11464	2 x 0,5	8,5	41,0	129,0	20
11465	3 G 0,5	8,8	45,0	150,0	20
11466	4 G 0,5	9,6	54,0	170,0	20
11467	5 G 0,5	10,2	66,0	199,0	20
11469	7 G 0,5	11,1	79,0	235,0	20
11472	12 G 0,5	14,0	137,0	320,0	20
11475	18 G 0,5	16,2	156,0	428,0	20
11478	25 G 0,5	19,2	250,0	503,0	20

Part No.	No. cores x cross-sec. mm ²	Outer \emptyset app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11489	2 x 0,75	8,8	46,0	143,0	18
11490	3 G 0,75	9,3	57,0	155,0	18
11491	4 G 0,75	9,9	63,0	190,0	18
11492	5 G 0,75	10,8	76,0	228,0	18
11494	7 G 0,75	11,5	100,0	323,0	18
11498	12 G 0,75	14,6	175,0	410,0	18
11501	18 G 0,75	17,1	240,0	560,0	18
11504	25 G 0,75	20,3	306,0	730,0	18
11516	2 x 1	9,4	54,0	150,0	17
11517	3 G 1	9,8	64,0	163,0	17
11518	4 G 1	10,4	76,0	200,0	17
11519	5 G 1	11,4	89,0	239,0	17
11521	7 G 1	12,5	114,0	289,0	17
11525	12 G 1	15,7	186,0	464,0	17
11528	18 G 1	18,4	284,0	628,0	17
11532	25 G 1	21,8	387,0	855,0	17
11546	2 x 1,5	10,4	64,0	162,0	16
11547	3 G 1,5	11,1	82,0	187,0	16
11548	4 G 1,5	11,8	99,0	240,0	16
11549	5 G 1,5	13,1	123,0	289,0	16
11551	7 G 1,5	14,2	148,0	383,0	16
11556	12 G 1,5	18,4	274,0	592,0	16
11559	18 G 1,5	21,5	386,0	806,0	16
11563	25 G 1,5	25,6	531,0	1241,0	16

Dimensions and specifications may be changed without prior notice. (RA01)

Continuation ▶

JZ-600-Y-CY flexible, number coded, 0,6/1kV, Cu screened

meter marking, EMC-preferred type



Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11574	2 x 2,5	11,8	110,0	272,0	14
11575	3 G 2,5	12,7	148,0	298,0	14
11576	4 G 2,5	13,8	169,0	345,0	14
11577	5 G 2,5	15,1	220,0	427,0	14
11578	7 G 2,5	16,3	284,0	561,0	14
11580	12 G 2,5	21,3	470,0	857,0	14
11582	18 G 2,5	25,4	572,0	1355,0	14
11584	25 G 2,5	30,0	740,0	1995,0	14
11590	2 x 4	14,2	124,0	306,0	12
11591	3 G 4	15,1	178,0	391,0	12
11592	4 G 4	16,2	234,0	527,0	12
11593	5 G 4	18,0	284,0	700,0	12
11594	7 G 4	19,8	321,0	920,0	12
11596	12 G 4	25,8	581,0	1510,0	12
11597	2 x 6	15,9	176,0	420,0	10
11598	3 G 6	16,9	245,0	629,0	10
11599	4 G 6	18,7	316,0	731,0	10
11600	5 G 6	20,4	442,0	1105,0	10
11601	7 G 6	22,2	530,0	1465,0	10
11602	2 x 10	18,3	260,0	845,0	8
11603	3 G 10	19,2	367,0	1125,0	8
11604	4 G 10	21,2	549,0	1345,0	8
11605	5 G 10	23,2	604,0	1635,0	8
11606	7 G 10	26,8	820,0	2210,0	8
11607	2 x 16	22,8	491,0	1150,0	6
11608	3 G 16	24,7	653,0	1395,0	6
11609	4 G 16	27,0	807,0	1870,0	6

Part No.	No. cores x cross-sec. mm ²	Outer ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
11610	5 G 16	30,0	940,0	2720,0	6
11611	7 G 16	32,2	1345,0	3213,0	6
11612	3 G 25	29,2	920,0	2465,0	4
11613	4 G 25	32,0	1169,0	2750,0	4
11614	5 G 25	35,7	1420,0	3490,0	4
11615	7 G 25	39,0	1921,0	4980,0	4
11616	3 G 35	32,3	1250,0	3230,0	2
11617	4 G 35	35,8	1680,0	4100,0	2
11618	5 G 35	39,5	2020,0	4950,0	2
11619	3 G 50	39,7	1887,0	4590,0	1
11620	4 G 50	43,4	2370,0	5780,0	1
11621	5 G 50	47,8	2880,0	7210,0	1
11622	3 G 70	44,9	2516,0	5610,0	2/0
11623	4 G 70	49,1	3257,0	7480,0	2/0
11624	5 G 70	53,8	4032,0	9390,0	2/0
11625	3 G 95	49,6	3086,0	8585,0	3/0
11626	4 G 95	54,1	4060,0	10220,0	3/0
11627	5 G 95	57,7	5244,0	13800,0	3/0
11628	3 G 120	51,5	4176,0	11105,0	4/0
11629	4 G 120	59,4	5231,0	13750,0	4/0
13137	4 G 150	67,9	7760,0	15990,0	300 kcmil
13147	4 G 185	74,0	7760,0	18470,0	350 kcmil

Dimensions and specifications may be changed without prior notice. (RA01)

Our Service on the Internet

The screenshot shows the HELUKABEL website interface. At the top, there is a navigation menu with links for Download centre, Logistic centre, Company, Products, Quality, News, Contact, Service, Opinion, and Imprint. A search bar is located on the right. Below the navigation, there is a breadcrumb trail: You are here: Home > Contact > Contact person. A dropdown menu is open under 'Contact person', listing Subsidiaries and Agencies, Headquarters Hemmingen, Approach, and Contact person. A 'Contact person' section is visible, with the text 'In order to respond to you request for: HELUKABEL® contact person in'. Below this, there is a 'Post code search for Germany:' section with an input field and a button 'Finden Sie Ihren Ansprechpartner'. On the right, there is a 'HELUKABEL world-wide' section with a world map and a 'please select...' dropdown menu.

Contact person

Enter your postal code to find out your personal customer sales consultant, who serves as your contact for questions and offers. Simply click and check it out. We are looking forward to hearing from you.

www.helukabel.de